



ORDERING CODE

AF ↑ Model	2000 ↑ Body size	02 ↑ Port size	□ ↑ Drain type
Air Fitter	1000	M5:M5 × 0.8	Blank: Differential
	2000	01:G1/8	pressure drain
	3000	02:G1/4	M: Manual drain
	4000	03:G3/8	A: Auto drain
	5000	04:G1/2	
		06:G3/4	
		10:G1	

Graphic Symbol



Remark:

Pls feel free to contact us if you have any customized request.


FEATURES

1. Prepare air for all types of compressed air tools and equipment
2. Compressed air with filters to remove solid particles and condensate
3. Protect your pneumatic tools for longer lifespan

DATA SHEET

Type-name	Air Filter									
Model	AF1000-M5	AF2000-01	AF2000-02	AF3000-02	AF3000-03	AF4000-03	AF4000-04	AF4000-06	AF5000-06	AF5000-10
Port Size (G)	M5*0.8	1/8	1/4	1/4	3/8	3/8	1/2	3/4	3/4	1
Cup Protective Cover	AF1000-2000 (W/O)			AF3000-5000 (W)						
Drain Type	Manual drain,auto drain and differential pressure drain (optional)									
Grade Of Filtration	5m ,25m,40m optional									
Working Medium	Air									
Operating Temperature Range	5-60 ℃									
Filter Cup Capacity	10	15	15	20	20	45	45	45	130	130
L-type Bracket	L10	L20	L20	L30	L30	L40	L40	L50	L50	L60
Material	Housing: Aluminum die-casting molding; Container cup: PE; Protective cover: iron									
Weight	100g	160g	160g	320g	320g	580g	580g	630g	1080g	1080g

STRUCTURE



AF1000~2000

Model	Port size	A	B	C	D	E	F	G	H	J	L	M	P
AF1000	M5	25	66	7	25	-	-	-	-	-	-	-	26.5
AF2000	1/8-1/4	40	97.5	11	40	17	30	27	22	5.4	40	2.3	40
AF3000	1/4-3/8	53	132.5	14	53	16	41	40	23	6.5	53	2.3	56
AF4000	3/8-1/2	70	168.5	18	70	17	50	54	26	8.5	70	2.3	73
AF4000-06	3/4	75	172.5	20	70	14	50	54	25	8.5	70	2.3	73
AF5000	3/4-1	90	247.5	24	90	23	66.5	66	35	11	90	3.2	90